

## LIGHT WOOD | LAMINATE | ACOUSTITECH LEAD 6, ACOUSTIVIBE SYSTEM (SOPREMA), ACOUSTITECH SOFIX, 5/8" PLYWOOD, RSIC-1 (PAC INTERNATIONAL) | FLOATING

Acoustic performance

AllC: 62 to 65

ASTC: 61 to 63

### ASSEMBLY DETAILS

#### STRUCTURE

Light wood

#### ASSEMBLY COMPONENTS

AcoustiTECH Lead 6, Acoustivibe System (Soprema), AcoustiTECH SOFIX, 5/8" plywood, RSIC-1 (PAC International)

#### FLOOR TYPE

Laminate

#### INSTALLATION TYPE

Floating

#### CEILING TYPE

Acoustic insulator

#### NUMBER OF GYPSUM

2



AUSSI DISPONIBLE  
ALSO AVAILABLE

#### \*OTHER CEILING ISOLATORS AVAILABLE:

- [RSIC-1](#)
- [RC-1 BOOST](#)
- [TECSOUND CLG 3900](#)

#### ACOUSTITECH LEAD 6



Plus de détails

#### ACOUSTIVIBE SYSTEM (SOPREMA)



Plus de détails

#### ACOUSTITECH SOFIX



Plus de détails

#### RSIC-1 (PAC INTERNATIONA L)



Plus de détails