# LIGHT WOOD | LAMINATE | 1“1/2 CONCRETE TOPPING, 5/8“ T&G PLYWOOD, INSONOFLOOR (SOPREMA), INSONOMAT (SOPREMA), RC-1 BOOST (PAC INTERNATIONAL) | FLOATING

Acoustic performance
AIIC: 57 to 61
ASTC: 58 to 62




## ASSEMBLY DETAILS

### STRUCTURE

Light wood

### ASSEMBLY COMPONENTS

1“1/2 concrete topping, 5/8“ T&G plywood, Insonofloor (Soprema), Insonomat (Soprema), RC-1 Boost (PAC International)

### FLOOR TYPE

Laminate

### INSTALLATION TYPE

Floating

### CEILING TYPE

Resilient channels

### NUMBER OF GYPSUM

2

### *OTHER MEMBRANES AVAILABLE :

The Insonomat membrane (Soprema) can be substituted with the Silentcrete membrane (Soprema) and the Silent Floor Pur membrane *(See assembly picture above).*

*Perimeter decoupling: The use of Silent Edge (Rothoblaas) is strongly recommended to prevent lateral vibration transfer.

**INSONOFLOOR (SOPREMA)**



Plus de détails

**INSONOMAT (SOPREMA)**



Plus de détails

**RC-1 BOOST (PAC INTERNATIONAL)**



Plus de détails