LIGHT WOOD | WOOD | 1“1/2 CONCRETE TOPPING, 5/8“ T&G PLYWOOD, INSONOFLOOR (SOPREMA), INSONOMAT (SOPREMA), RC-1 BOOST (PAC INTERNATIONAL) | FLOATING

Acoustic performance
AIIC: 57 to 61
ASTC: 58 to 62



ASSEMBLY DETAILS

STRUCTURE

Light wood

ASSEMBLY COMPONENTS

1“1/2 concrete topping, 5/8“ T&G plywood, Insonofloor (Soprema), Insonomat (Soprema), RC-1 Boost (PAC International)

FLOOR TYPE

Wood

INSTALLATION TYPE

Floating

CEILING TYPE

Resilient channels

NUMBER OF GYPSUM

2

*OTHER MEMBRANES AVAILABLE :

The Insonomat membrane (Soprema) can be substituted with the Silentcrete membrane (Soprema) and the Silent Floor Pur membrane *(See assembly picture above).*

**Perimeter decoupling: The use of Silent Edge (Rothoblaas) is strongly recommended to prevent lateral vibration transfer.*

INSONOFLOOR (SOPREMA)



Plus de détails

INSONOMAT (SOPREMA)



Plus de détails

RC-1 BOOST (PAC INTERNATIONAL)



Plus de détails