

LIGHT WOOD | WOOD | INSONOMAT (SOPREMA), INSONOFLOOR (SOPREMA), 1"1/2 CONCRETE TOPPING, 5/8" T&G PLYWOOD, RC-1 BOOST (PAC INTERNATIONAL) | FLOATING

Acoustic performance

AllC: 57 to 61

ASTC: 58 to 62

ASSEMBLY DETAILS

STRUCTURE

Light wood

ASSEMBLY COMPONENTS

Insonomat (Soprema), Insonofloor (Soprema), 1"1/2 concrete topping, 5/8" T&G plywood, RC-1 Boost (PAC International)

FLOOR TYPE

Wood

INSTALLATION TYPE

Floating

CEILING TYPE

Resilient channels

NUMBER OF GYPSUM

2



*OTHER MEMBRANES AVAILABLE :

The Insonomat membrane (Soprema) can be substituted with the Silentcrete membrane (Soprema) and the Silent Floor Pur membrane (See assembly picture above).

**Perimeter decoupling: The use of Silent Edge (Rothoblaas) is strongly recommended to prevent lateral vibration transfer.*

INSONOMAT (SOPREMA)



Plus de détails

INSONOFLOOR (SOPREMA)



Plus de détails

RC-1 BOOST (PAC INTERNATIONA L)



Plus de détails

