

LIGHT WOOD | WOOD | 1"1/2 CONCRETE TOPPING, 5/8" T&G PLYWOOD, ACOUSTITECH LEAD 3.3, INSONOMAT (SOPREMA), RC-1 BOOST (PAC INTERNATIONAL) | DOUBLE GLUED DOWN

Acoustic performance
 AIIIC: 54 to 58
 ASTC: 58 to 62

ASSEMBLY DETAILS

STRUCTURE

Light wood

ASSEMBLY COMPONENTS

1"1/2 concrete topping, 5/8" T&G plywood, AcoustiTECH Lead 3.3, Insonomat (Soprema), RC-1 Boost (PAC International)

FLOOR TYPE

Wood

INSTALLATION TYPE

Double glued down

GLUE

Adhesive AD-532+, Adhesive AD-316, Adhesive AD-844 MS

CEILING TYPE

Resilient channels

NUMBER OF GYPSUM

2



*OTHER MEMBRANES AVAILABLE :

The Insonomat membrane (Soprema) can be substituted with the Silentcrete membrane (Soprema) and the Silent Floor Pur membrane (See assembly picture above).

**Perimeter decoupling: The use of Silent Edge (Rothoblaas) is strongly recommended to prevent lateral vibration transfer.*

ACOUSTITECH LEAD 3.3



Plus de détails

ADHESIVE AD-532+



Plus de détails

ADHESIVE AD-316



Plus de détails

ADHESIVE AD-844 MS



Plus de détails

INSONOMAT (SOPREMA)



Plus de détails

RC-1 BOOST (PAC INTERNATIONAL)



Plus de détails

www.acousti-tech.com