LIGHT WOOD | WOOD | 1“1/2 CONCRETE TOPPING, 5/8“ T&G PLYWOOD, ACOUSTITECH LEAD 3.3, INSONOMAT (SOPREMA), RC-1 BOOST (PAC INTERNATIONAL) | DOUBLE GLUED DOWN

Acoustic performance
AIIC: 54 to 58
ASTC: 58 to 62



ASSEMBLY DETAILS

STRUCTURE

Light wood

ASSEMBLY COMPONENTS

1“1/2 concrete topping, 5/8“ T&G plywood, AcoustiTECH Lead 3.3, Insonomat (Soprema), RC-1 Boost (PAC International)

FLOOR TYPE

Wood

INSTALLATION TYPE

Double glued down

GLUE

Adhesive AD-532+, Adhesive AD-316, Adhesive AD-844 MS

CEILING TYPE

Resilient channels

NUMBER OF GYPSUM

2

*OTHER MEMBRANES AVAILABLE :

The Insonomat membrane (Soprema) can be substituted with the Silentcrete membrane (Soprema) and the Silent Floor Pur membrane *(See assembly picture above).*

**Perimeter decoupling: The use of Silent Edge (Rothoblaas) is strongly recommended to prevent lateral vibration transfer.*

ACOUSTITECH LEAD 3.3	ADHESIVE AD-532+	ADHESIVE AD-316	ADHESIVE AD-844 MS	INSONOMAT (SOPREMA)	RC-1 BOOST (PAC INTERNATIONAL)
					
Plus de détails	Plus de détails	Plus de détails	Plus de détails	Plus de détails	Plus de détails