LIGHT WOOD | WOOD | 1“1/2 CONCRETE TOPPING, 5/8“ T&G PLYWOOD, ACOUSTITECH LEAD 3.3, ACOUSTIVIBE SYSTEM (SOPREMA), INSONOMAT (SOPREMA), RSIC-1 (PAC INTERNATIONAL) | DOUBLE GLUED DOWN

Acoustic performance
AIIC: 57 to 61
ASTC: 58 to 62



ASSEMBLY DETAILS

STRUCTURE

Light wood

ASSEMBLY COMPONENTS

1“1/2 concrete topping, 5/8“ T&G plywood, AcoustiTECH Lead 3.3, Acoustivibe System (Soprema), Insonomat (Soprema), RSIC-1 (PAC International)

FLOOR TYPE

Wood

INSTALLATION TYPE

Double glued down

GLUE

Adhesive AD-532+, Adhesive AD-844 MS, Adhesive AD-316

CEILING TYPE

Acoustic insulator

NUMBER OF GYPSUM

2

*OTHER MEMBRANES AVAILABLE :

The Insonomat membrane (Soprema) can be substituted with the Silentcrete membrane (Soprema) and the Silent Floor Pur membrane *(See assembly picture above).*

**Perimeter decoupling: The use of Silent Edge (Rothoblaas) is strongly recommended to prevent lateral vibration transfer.*

*OTHER CEILING ISOLATORS AVAILABLE:

- RSIC-1
- RC-1 BOOST
- TECSOUND CLG 3900

ACOUSTITECH LEAD 3.3	ADHESIVE AD-532+	ADHESIVE AD-844 MS	ACOUSTIVIBE SYSTEM (SOPREMA)	ADHESIVE AD-316	INSONOMAT (SOPREMA)	RSIC-1 (PAC INTERNATIONAL)
						
Plus de détails	Plus de détails	Plus de détails	Plus de	Plus de détails	Plus de détails	Plus de détails

détails

www.acousti-tech.com