LIGHT WOOD | CERAMIC | 1“1/2 CONCRETE TOPPING, 5/8“ T&G PLYWOOD, ACOUSTITECH CERAMIC, FLEXIBLE MORTAR, MORTAR, ACOUSTIVIBE SYSTEM (SOPREMA), INSONOMAT (SOPREMA), RSIC-1 (PAC INTERNATIONAL) | MORTAR

Acoustic performance
AIIC: 51 to 56
ASTC: 58 to 62



ASSEMBLY DETAILS

STRUCTURE

Light wood

ASSEMBLY COMPONENTS

1“1/2 concrete topping, 5/8“ T&G plywood, AcoustiTECH Ceramic, Flexible mortar, Mortar, Acoustivibe System (Soprema), Insonomat (Soprema), RSIC-1 (PAC International)

FLOOR TYPE

Ceramic

INSTALLATION TYPE

Mortar

GLUE

Adhesive AD-280

CEILING TYPE

Acoustic insulator

NUMBER OF GYPSUM

2

*OTHER MEMBRANES AVAILABLE :

The Insonomat membrane (Soprema) can be substituted with the Silentcrete membrane (Soprema) and the Silent Floor Pur membrane *(See assembly picture above).*

**Perimeter decoupling: The use of Silent Edge (Rothoblaas) is strongly recommended to prevent lateral vibration transfer.*

*OTHER CEILING ISOLATORS AVAILABLE:

- RSIC-1
- RC-1 BOOST
- TECSOUND CLG 3900

ACOUSTITECH CERAMIC	ADHESIVE AD-280	ACOUSTIVIBE SYSTEM (SOPREMA)	INSONOMAT (SOPREMA)	RSIC-1 (PAC INTERNATIONAL)
				
Plus de détails	Plus de détails	Plus de	Plus de détails	Plus de détails

détails

www.acousti-tech.com